



QUICK START GUIDE



FEATURES:

- 1/2.8" 2.0 MegaPixel Sony® Exmor™ Progressive Scan CMOS Sensor
- Up to 30fps live view @ 1920 x 1080p
- High speed PTZ operation from 0.1°/sec to 420°/sec.
- XDNR Noise Reduction (Utilizes both 2DNR & 3DNR)
- 16:9 Video format
- True Day/Night with ICR & DSS
- H.264/MJPEG Dual Streaming
- Full duplex 2 way audio, Alarm IN/OUT
- Minimal Latency w/Max 16 User Connections
- Onvif Compliance
- · MicroSD Card Slot supporting up to 64GB cards for Onboard EDGE Recording & Playback
- 12VDC & PoE Plus (Power over Ethernet)





1. Box Contents

- 1) VT-PTZ220N 20x IP PTZ Camera
- 2) Mounting Hardware & Accessories
- 4) ENVI Series CD

2. Included Accessories

Surface Mount Housing Qty: 1

Mounting screws Qty: 3

Alarm/Multi Cable Qty: 1

ENVI Series CD Qty: 1



eccumumum) eccumumum





3. Available Accessories

3.1. Optional Mounts & Housings



VT-PTWMT PTZ Wall Mount



VT-PTPPMT PTZ Parapet Mount



VT-PTIBMT PTZ I-Beam Mount



PTZ Pedestal / Ceiling Mount



VT-PTHSG/DIP PTZ Housing w/Clear or Smoked Bubble



VT-PTCNMT PTZ Corner Mount Adapter



VT-PTFMK PTZ Flush Mount Kit w/Clear or Smoked Bubble



VT-PTPLMT PTZ Pole Mount Adapter

4. VT-PTZ220N Installation

• Remove by unscrewing the surface mount housing (See Fig. A). Simultaneously push the right and left hooks from the camera, this will free the camera from the base. (See Fig. B)



4.1. Surface mount Installation

• Attach the PTZ Dome camera base to a sturdy surface with two of the included St4x30 screws.



4.2. Connections



1. Power

Depending on the type of installations, apply power to the camera by one of the two options below.

- a) Via Ethernet Use only with POE + switch (100 Meters max distance)
- b) 12VDC Use with 12VDC 2A ** SEE IMPORTANT NOTES BELOW **

Primary and secondary grounds are completely isolated to avoid possible ground-loop problems.

2. Ethernet Connection

Insert one end of the Ethernet cable into the network jack of your camera, and insert the other end into the data port (switch, router, etc)



4.3. Removable Storage

For recording directly on the camera you will need to install a MicroSD card, this will allow you to play video directly from the camera. (*Please use only class 10 SD cards*).

 a) Insert the MicroSD memory card as shown below (the MicroSD card will need to be formatted . (refer to Section Error! Reference source not found. Error! Reference source not found. on page Error! Bookmark not defined. for instructions on Formatting)



4.4. Attaching PTZ Camera to Base

a) Place the camera on to the Guide and push upwards, you will hear a click from the camera snapping in to the base.



b) Screw back the Surface Mount Housing in to Place.



5. Camera Software Installation

1. Run **IP Installer** Software from the CD program on a computer that is on the same network as the IP camera.



2. Start IP Installer, by double clicking the icon "IP Installer"



3. After the program has started, the main window of **IP Installer** program will appear on the screen as shown below.

Q 🍠	۵ % 😚	1	Filter : All			
Model	MAC address	IP address	IP Ty Server name	HTTP port	Version	Status

 Search for the installed camera on the network by clicking the search product icon, the camera should appear as the image below. The default IP address is 10.20.30.40

IP Installer (v3.0.6)	-		1.000				>
Q 🖉 🔅	**		Filter :	All			
Aodel M	IAC address	IP address	IP Ty	Server name	HTTP port	Version	Status
TD-13VN 10	7C45020083	10.0.0.50	static	Network Video System	80	4.14-01-ds	Success
TD-13VN 10	Please, wait	10.0.0.50 for a while. (It dep	static ends on your r	Network Video System	80 Cancel	4.14-01-ds	Succes

To assign an automatic IP address to this camera within the network, click the "Automatic IP Setup" icon

과 IP Installer (v3.0.6)	1	1.000.7	and the second division of	ALC: NOT		- • ×
Q 🟉	0%0	• 7	Filter :	All			
Model	MAC address	IP address	IP Ty	Server name	HTTP port	Version	Status
VTD-13VN	1C7C45020083	10.0.0.50	static	Network Video System	80	4.14-01-ds	Success

Verify the Automatic IP address provided, enter the default password root and then click Set as shown below.

Mac Address	107045020083	Server Name Netwo	rk video Syst	tem V H	TIP Port 80	
IP Type	- r	Static	DHCP	0	PPPoE	
Network	IP Address	10 . 0 . 0 . 50	PPPoE L			
	Netmask	255 . 255 . 255 . 0	PPPoE Password PPPoE Password Confirm			
	Default Gateway	10 . 0 . 0 . 1				
	DNS1	168 . 126 . 63 . 1				
	DNS2	168 . 126 . 63 . 2				
Wireless inform	mation					
Auth Mode		Ŧ	ESSID	Scan AP		
Encryption	None W	EP O TKIP O AES				
WEP Mode	-	-				
ŒY1	0					
ŒY2						
ŒY3						
ŒY4						
NPAPSK			j l			
Authentication Admin Passwor	rd		1			
Save Control in	ation Option		-			

After the camera was configured by the program automatically, you will be able to get access by

 Right click over the camera information, "Go Product Homepage"



b) Click over the icon "Connect Product Homepage"



8. From the Home Page, you can "Live View" or administrate "Admin" the camera.



Homepage ver 4.16-B2_VI for Network Video System

On Live View you will be able to see live video from your camera.





Version 1.0