



Also Available in Charcoal Gray (VTC-TNT2HR4F2B)



FEATURES:

- 1/3" 4.0 Megapixel Progressive Scan CMOS image sensor
- Up to 30fps live view @ 4 MegaPixel (2592x1520)
- 2.8mm Fixed Iris Lens Included
- 2 High Power Infrared LED's with 65' IR Range
- 120dB Super Wide Dynamic Range (WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR (2D-DNR & 3D-DNR) Noise Reduction
- On Board Motion Detection
- H.265/H.264/MJPEG Triple Streaming
- Secondary Video Output (CVBS)
- Remote Viewing via CMS, Internet Explorer, and iOS & Android Apps
- Minimal Latency with up to 10 simultaneous user connections
- ONVIF Compliant
- IP66 Weather Resistance
- Optional Junction Box Mount Available (VT-TJB01)
- Available in Ivory or Charcoal Gray
- 12VDC & PoE (Power over Ethernet) Operation

Transcendent Series High Definition 4 Megapixel IP Network Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, IP Network Cameras transmit over remote viewing via CMS, Internet Explorer, and iOS & Android Apps.

Use with VITEK Transcendent Series Real Time Network Video Recorders




Transcendent Series 4, 8, 32, and 64 Channel 5 MegaPixel H.265 Real Time Network Video Recorders with 4K HDMI Output.



Detailed Specifications

Image Sensor	1/3" 4.0 Megapixel Progressive Scan CMOS
Image Size	4 MegaPixel 2592x1520
Resolution	4 MP (2592x1520) / 3 MP (2304x1296) / 1080P (1920x1080) / 720P (1280x720) / D1/CIF (480x240)
Min. Illumination	0 Lux (IR LED ON)
Lens	2.8mm Fixed Iris Lens Included
Day/Night	True Day/Night by ICR
IR LEDs	2 x High Power
IR Distance	65'
Video Compression	H.265 / H.264 / MJPEG
Audio Compression	G.711A / G.711U
Multi-Stream	1~30fps: 4 MP, 3 MP, 1080P, 720P, D1, CIF, 480x240
WDR	120dB Super WDR
DNR	XD-DNR (2D-DNR & 3D-DNR)
Quality	VBR (Five Levels of Adjustment) / CBR (Adjustable)
Image Setting	Saturation, Brightness, Contrast, WDR, Noise reduction
Smart Alarm	Motion Alarm
ROI	Max 8 detailed areas can be viewed
Network	RJ45
Video Output	1 x BNC (CVBS)
Audio	1 x IN (One-way Audio)
Remote Viewing	CMS / Web Browser / Mobile (iOS/Android)
Supported Browsers	IE / Chrome / Firefox / Safari
Connection Protocol	ONVIF
Weather Resistance	IP66
Power Input	12VDC / PoE
Power Consumption (12VDC)	210mA (IR Off) / 420mA (IR On)
Power Consumption (PoE)	4W (IR's off) / 6.7W (IR's on)
Working Environment	-4 ~ 122 / 10% ~ 90% Humidity
Weight	13.05 oz. / 0.82 lbs. / 370g
Dimensions	3.43" x 4.25" (87 x 108mm) Dia x H



VT-TJB01

Optional Junction Box for Cable Management for use with all Transcendent Bullet and Turret Style Cameras