





















FEATURES:

- 1/3" 2.1 MegaPixel CMOS Sensor
- HD-TVI & AHD/CVBS Video Output
- 3.6mm Fixed Iris Lens Included
- 42 Infrared LED's with 150' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- 3D-DNR Noise Reduction
- IP66 Weather Resistance
- Supports Up The COAX Control
- Over 1500' HD Video Transmission (Depending on cable characteristics and integrity)
- Optional Junction Box Mount Available (VT-TJB01)
- 12VDC Operation

Transcendent Series High Definition 1080P HD-TVI, AHD, CVBS Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, analog HD Cameras transmit over your existing Coaxial cable at distances up to 1500'.

5-In-1 Digital Video Recorders Supporting HD-TVI / AHD / CVI / 960H Cameras



Transcendent Series 4, 8, 16 or 32 Channel 5-In-1 Digital Video Recorders Support HD-TVI / AHD / CVI / 960H Cameras as well as IP Cameras with Full 1080P Recording & Playback.





VTC-TTAB42R2F

Specifications	
Image Sensor	1/3" 2.1 MegaPixel CMOS Sensor
Resolution	HD-TVI & AHD: 1080p (2.1 MegaPixel) / CVBS: 960H
Effective Pixels	1920(H) x 1080(V)
Signal System	PAL/NTSC PAL/NTSC
Video Output	1x HD-TVI (BNC) & 1 AHD/CVBS (BNC)
Lens	3.6mm Fixed
Day/Night	True Day/Night by ICR
S/N Ratio	>52dB (AGC OFF)
Auto Gain Control	0FF ∼44.8dB
Min Illumination	0 Lux (LED ON)
IR LEDs	42
IR Distance	150'
Color-B/W Auto Switch	Yes
Electronic Shutter	1/50s~ 1/67500s
White Balance	AWB
WB Range	2300~9600K
BLC	Yes
WDR	Digtial WDR
Transmission Distance	Up to 1500' (Depending on cable characteristics & integrity)
Up the COAX Control	YES
Noise Reduction	Yes
Weather Resistance	IP66
Power Consumption	210mA (IR Off) / 420mA (IR On)
Power Supply	12VDC
Working Environment	-4~122 / 10%~90% Humidity
Weight	20.81 oz. / 1.30 lbs. / 590g
Dimensions	3.43 x 8.62" (87mm x 219mm) Dia x L

























Optional Junction Box for Cable Management for use with all Transcendent Bullet and Turret Style Cameras



