

VTD-TND30R5V2

Transcendent 5 Megapixel Outdoor WDR IP Vandal Dome Camera with 30 IR LEDs



Also Available in Charcoal Gray (VTD-TND30R5V2B)



FEATURES:

- 1/1.8" 5.0 Megapixel Progressive Scan CMOS image sensor
- Advanced Starlight Technology Offers Dramatically Higher Sensitivity to Light Producing Color Images in Very Dark & Night Scenes
- Up to 30fps live view @ 5 MegaPixel (2592x1944)
- 3.6~10mm Varifocal Lens
- 30 Infrared LED's with 100' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR (2D-DNR & 3D-DNR) Noise Reduction
- On Board Motion Detection
- H.265/H.264/MJPEG Triple Streaming
- Secondary Video Output (CVBS)
- Remote Viewing via CMS, Internet Explorer, and iOS & Android Apps
- Minimal Latency with up to 10 simultaneous user connections
- IP66 Weather Resistance & IK10 Impact Resistance Rating
- MicroSD memory card slot for Local recording supporting up to 128GB MicroSDXC cards
- ONVIF Compliant
- Optional Wall Mount (VT-TWM03) & Junction Box Mount Available (VT-TJB02)
- Available in Ivory or Charcoal Gray
- 12VDC & PoE (Power over Ethernet) Operation

Transcendent Series High Definition 5 Megapixel IP Network Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, IP Network Cameras transmit over remote viewing via CMS, Internet Explorer, and iOS & Android Apps.

Use with VITEK Transcendent Series Real Time Network Video Recorders



Transcendent Series 4, 8, 32, and 64 Channel 5 MegaPixel H.265 Real Time Network Video Recorders with 4K HDMI Output.



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On Innovation

VTD-TND30R5V2

Transcendent 5 Megapixel Outdoor WDR IP Vandal Dome Camera with 30 IR LEDs

Detailed Specifications

Image Sensor	1/1.8" 5.0 Megapixel Progressive Scan CMOS with Advanced Starlight Technology
Image Size	5 MegaPixel 2592x1944
Resolution	5 MP (2592x1944), 4 MP (2560x1440) / 1080P (1920x1080) / 720P (1280x720) / D1/CIF (480x240)
Min. Illumination	0 Lux (IR LED ON)
Lens	3.6~10mm (Vari-Focal)
Day/Night	True Day/Night by ICR
IR LEDs	30
IR Distance	100'
Video Compression	H.265 / H.264 / MJPEG
Audio Compression	G.711A / G.711U
Multi-Stream	1~30fps: 5 MP, 4 MP, 1080P, 720P, D1, CIF, 480x240
WDR	D-WDR
DNR	XD-DNR (2D-DNR & 3D-DNR)
Quality	VBR (Five Levels of Adjustment) / CBR (Adjustable)
Image Setting	Saturation, Brightness, Contrast, WDR, Noise reduction
Smart Alarm	Motion Alarm / Sensor Alarm
ROI	Max 8 detailed areas can be viewed
Network	RJ45
Video Output	1 x BNC (CVBS)
Audio	1 x IN & 1 x OUT (Two-Way Audio)
Storage Card	MicroSD up to 128GB
RS485	x 1
Alarm Input	x 1
Alarm Output	x 1
Remote Viewing	CMS / Web Browser / Mobile (iOS/Android)
Supported Browsers	IE / Chrome / Firefox / Safari
Connection Protocol	ONVIF
Resistance Rating	IP66 / IK10
Power Input	12VDC / PoE
Power Consumption (12VDC)	250mA (IR Off) / 460mA (IR On)
Power Consumption (PoE)	4W (IR's off) / 6.7W (IR's on)
Working Environment	-4~122 / 10%~90% Humidity
Weight	34.22 oz. / 2.14 lbs. / 970g
Dimensions	5.91" x 4.49" (150 x 114mm) Dia x H



VT-TWM03

Wall Mount for Transcendent 30 IR LED Vandal Domes and Varifocal Turret Cameras



VT-TJB02

Junction Box for Cable Management for use with Transcendent 30 IR LED Vandal Domes



(888) VITEK-70 | WWW.VITEKCCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On Innovation