



## FEATURES

- Provides 8 - 10/100Base-TX PoE ports & 2 10/100/1000Base-TX Ethernet Uplink Ports
- 120 Watt PoE Power Budget
- Conforms to PoE Standard: IEEE802.3af, IEEE802.3at
- High back-plane bandwidth 5.6Gbps
- IEEE802.3x Flow control
- EMI standards complies with FCC, CE class B
- Surge Protection for Power and Data Ports

VT-8P120 Specifications	
Ethernet Speed	8x PoE Ports: 10/100/1000Mbps / 2x Uplink Ports:10/100/1000Mbps
Ethernet Transmission Distance	328 feet (100 Metres)
Ethernet Standard	PoE Standard: IEEE802.3af, IEEE802.3at
Switching capacity	5.6G
Transfer Rate	14,880 pps @ 10Mbps / 148,800 pps @ 100Mbps / 1,488,000 pps @ 1000Mbps
MAC Address	4K MAC address table
Power Supply	External Power Adaptor
Voltage Range	52~ 55 VDC
Power Consumption	70W (67W for PoE)
Working Temperature	32°~104°F (0°~40°C) / 20~85% RH
Dimensions (W x H x D)	7.48" x 3.94" x 1.10" (190 x 100 x 28mm)