

The VT-DVR04 four channel DVR combines high quality digital video recordings with the operating ease of a VCR. It's capable of delivering images with resolution above that of super VHS with versatile recording modes from 1 to 60 images per second.


00.00.23

00.00.24

00,00,29



VT-DVRO4
NTSC
4 Video Input, Composite BNC
Playback (BNC), Playback (RCA), and Input Video Loopback (BNC)
2-Channel Monaural Recording (RCA)
Monaural Playback (RCA)
RJ-45 for Ethernet
IR Sensor Extension Slot
Terminal Block, Max 1A, 5 or 12 Volt High Active
Terminal Block (Normal Open)
RS-485 or RS-232C (Switch Selectable)
Sync Pulse for Camera Switch (Active Low TTL Level, 1 Pulse Every 1 Second)
USB Memory Can Be Connected for Compressed Video Export and Program Download
Real-Time Recording for All 4 Channels
Field: 720X240, Frame: 720X480
5 Levels
MPEG-2
Continuous, Alarm, Motion Detection,and No Recording
2-Channels, Monaural, Records ONLY with 15FPS or Higher Recording Speed
Time/Date
Forward (X1 to X8), Reverse (X1 to X8), Still Advance
60GB Default, Space for 1 Additional Hard Drive
Compressed Data Export (for ~3 secs of footage)
ISDN, xDSL
For Live Video Monitoring, Recorded Video Transmission and Playback, File Playback and Configuration Change
100 VAC- 250 VAC
30 Watts





9970 GLENOAKS BLVD. UNIT B SUN VALLEY, CA 91352 PHONE: 888-VITEK-70 818-771-0300 FAX: 818-771-0400 WWW.VITEKCCTV.COM

41°F to 104°F (5°C to 40°C)

Operating Condition