

# VT-PTZ36W

36x Xpress Dome  
PTZ Camera with WDR  
& Image Stabilization



## FEATURES

- WDR True Day/Night PTZ Camera
- Built-in 3.4-122.4mm Lens with 36x Optical Zoom / 12x Digital Zoom
- 550 TV Lines of Resolution
- Auto Protocol Detection
- 248 Presets programmed with view direction, zoom, BLC.
- 4 Patterns record and play back user preference of surveillance path up to 240° sec.
- 16 Scans, 1 Auto Pan: 8 speed steps from slow to medium panning with smooth Vector Scan.
- 8 Tours: Each tour consists up to 64 Preset, Pattern, Scan and other Tours.
- Tour can be expanded up to 500 different functions using nested Tours.



**VT-PTPPMT**  
Parapet Roof  
Mount



**VT-PTPDMT**  
Pedestal /  
Ceiling Mount



**VT-PTCNMT**  
Corner Mount  
Adapter



**VT-PTWMT**  
Wall Mount



**VT-PTPLMT**  
Pole Mount  
Adapter



**VT-PTODKIT**  
Outdoor Kit  
w/Alarm, Heater,  
Blower, & Sun  
Shield



**VT-PTFMK**  
Flush In-Ceiling  
Mount Kit  
w/Clear or  
Smoked Bubble



**VT-PTHSG**  
Indoor/Outdoor  
Housing w/Clear  
or Smoked  
Bubble



**VT-KBD1**  
Xpress Keyboard

- 3-Axis 64 Step Variable-Speed Joystick
- Auto Focus with Manual Override
- Large 1 1/2" x 5 3/16" LCD display
- Control up to 256 Devices including Xpress Domes and VITEK Saga Series Digital Video Recorders
- Digital Flip to follow objects (Enable/Disable)
- 18 Programmable Functions (6 keys with 3 layers each)
- Recall 8 Pre-Programmed tours
- Recall up to 248 Preset Positions
- Built-in RS-485/422 half-duplex mode supports up to 64 devices. Simplex mode supports up to 256 devices.



(888) VITEK-70 | [WWW.VITEKCCTV.COM](http://WWW.VITEKCCTV.COM)  
28492 Constellation Road Valencia, CA 91355

CYAN

MAGENTA

YELLOW

BLACK

# VT-PTZ36W

36x Xpress Dome  
PTZ Camera with WDR  
& Image Stabilization

## Detailed Specifications

Image Sensor	1/4" Interline Transfer CCD
Effective Pixels	768(H) X 494(V)
Horizontal Resolution	550 TV Lines
Minimum Illumination	1.4 Lux (1/60 sec) / 0.01 Lux (F1.4 Slow Shutter)
Lens	F1.4 (f=3.4~122.4mm Optical) 36X Optical / 12X Digital
Angle of View	3.4mm - 57.8°(H) / 122.4mm - 1.7°(H)
Shutter Speed	NTSC - 1/4 ~ 1/10,000 Pal - 1/3~1/10,000
S/N Ratio	50dB
Video Output	1.0 Vp-p, 75 Ohm Composite
Sync System	Int/Ext, V-Phase Remote Control
Scanning System	2:1 Interface
Focus	Auto/Manual
White Balance	AUTO, ATW, Indoor, Outdoor, One Push, Manual, Outdoor Auto, Sodium Vapor Lamp (Fix/Auto)
Iris Control	Auto/Manual
Gain Control	Auto/Manual
BLC (Back Light Compensation)	ON/OFF
DNR (Digital Noise Reduction)	1~5 / OFF
DIS (Digital Image Stabilizer)	ON / OFF
WDR (Wide Dynamic)	ON/OFF/AUTO
Pan Travel	360° Continuous
Manual Pan Speed/sec	0.1~90°/sec
Preset Pan Speed/sec	380°/sec
Tilt Travel	-5°~90°/95°
Manual Tilt Speed/sec	0.1~90°/sec
Preset Tilt Speed/sec	380°/sec
Proportional Pan & Tilt	Yes
Preset Accuracy	0.2°
Communication	RS-422/485, 8bit, 1bit stop No Parity, 2.4~230Kbps
Preset	248 Position
Area Title	24 Area Names
Privacy Zone	8 Blocks in a screen
Title Character	16 Character
Tour	8 Tour
Pattern	4 (1 Full or 3, 240sec)
Auto Pan	16 Scan, 1 Auto Pan
Auto Flip	Digital Quick Turn
Alarm (Input/Output)	8/2
Certifications	FCC / CE Class A
Power	18~30VAC/ Surge Protection 24VAC/40VA or 24DC/3A
Dimensions (OD x H)	Pendant Mount: 4.96" x 7.13" / Flush Mount: 4.96" x 3.15"



(888) VITEK-70 | [WWW.VITEKCCTV.COM](http://WWW.VITEKCCTV.COM)  
28492 Constellation Road Valencia, CA 91355