

VT-SRL Series

Spire Series 4, 8, & 16 Channel
960H Digital Video Recorders




FEATURES

- Supports High Resolution 960H Cameras
- 4, 8 or 16 Video Inputs with 1 HDMI, 1 Spot Monitor Output, and 1 VGA output
- H.264 Compression
- Up to 480fps Live Display & 480fps Recording (VT-SRL916) / 240/240 (VT-SRL908) / 120/120 (VT-SRL904)
- Supports both Dynamic and Static IP Addresses
- 4 Alarm Inputs / 1 Relay Out
- Supports two internal Hard Drives (VT-SRL908/VT-SRL916) / One internal Hard Drive (VT-SRL904)
- Supports up to 4TB internal storage (1 x 4 TB HDD)
- 20 x 12 Motion Detection Grid
- Remote Viewing over the Internet, LAN, Explorer, Safari, Firefox, Opera and Chrome
- Applications for iPhone, iPad, iTouch and Android Devices
- Mac OSX Client & PC CMS Central Management Software Included
- Thumbnail Search
- Automatic sending of Health & Event notifications via email
- Control locally via USB Mouse or with the Included IR Remote control
- PTZ Control over RS-485



Intuitive configuration menu.




Remote Viewing over the Internet, LAN, Explorer, Safari, Firefox, Opera and Chrome



Remote Viewing Apps Available for iPhone, iPad & Android Devices



View backups on PC computers using included Backup Player Software



Included CMS Software allows remote viewing & control of multiple DVR's even when located at multiple locations!



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VT-SRL Series

Spire Series 4, 8, & 16 Channel 960H Digital Video Recorders

Detailed Specifications	VT-SRL904	VT-SRL908	VT-SRL916
Video Input	4 Channels	8 Channels	16 Channels
Video Compression	H.264	H.264	H.264
FPS (Display / Recording)	120 / 120 (CIF, 2CIF, D1, 960H)	240 / 240 (CIF, 2CIF, D1, 960H)	480 / 480 (CIF, 2CIF, D1, 960H)
Playback Rate	120FPS @ 960H / 120FPS @ CIF	240FPS @ 960H / 240FPS @ CIF	480FPS @ 960H / 480FPS @ CIF
Operating System	Linux		
Video Output	VGA / HDMI / Spot BNC		
Split-Screen	Live: 1, 4, SEQ, Playback: 1, 4	Live: 1,4,6,8,9, SEQ / Playback: 1, 4, 9	Live: 1, 4,6,8,9,16 SEQ / Playback: 1, 4,6,8,9,16
Audio In/Out	4 Line In (1/8") / 1 Line Out (1/8")		
Alarm In/Out	4 Alarm Inputs / 1 Outputs with 1 Relay		
Storage	1 Internal HDD (SATA)	2 Internal HDD (SATA)	2 Internal HDD (SATA)
Archive	USB Device & Network		
USB Port	2 Front USB Ports		
System Control	USB Mouse, Included IR Remote Control		
Network	TCP/IP, HTTP, DHCP (DDNS)		
RJ-45 Ethernet Port	10/100Mbps	10/100/1000Mbps	10/100/1000Mbps
Search	Thumbnail, Calendar, Event		
PTZ	1 - RS-485		
Recording Resolution Setting	By each camera for different resolution setting(CIF/2CIF/D1/960H)		
Recording Quality Control	4 Levels (Low/Standard/High/Highest)		
Recording Modes	Continuous, Schedule, Alarm, and Panic		
Panic Record	Overrides all other recording settings to provide the best quality recording		
Pre-recording	Max. 5 seconds		
Post-recording	Max. 180 seconds		
Motion Detection	Adjustable 20x12 Grid with 30 Steps Sensitivity Level		
Player	Backup player, and HDD PC Viewer		
E-mail notification	E-mails to specific users to notify events		
System Configuration	Full setup configuration over network		
Bandwidth limit	YES: Adjustable by User		
Two-Way Audio	YES		
Power	DC12V, Adaptor, 3.3A, 100~240V AC, 50-60Hz		
Operating Temperature	32° ~ 104°F (0° ~ 40°C)		
Humidity	10 ~ 90% NC		
Case Form Factor	1.0U		
Dimensions (W x H x D)	10" x 1.85" x 7.25"	12" x 1.85" x 12.25"	12" x 1.85" x 12.25"
Weight	3.3 lbs. (1.5kg)	6.85 lbs. (3.1kg)	6.85 lbs. (3.1kg)



VT-SRL904



VT-SRL908



VT-SRL916



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355