

Rear Camera Inputs




Optional Remote Control Available (VT-UTCC)

FEATURES

- 1/2.9" Sony® CMOS
- 2.1 MegaPixel With full 1080p/720p HD-SDI Output (SMPTE 292M)
- Smart Motion Zoom tracks motion, then intelligently zooms into that area of the frame
- Mechanical IR Cut Filter (True Day/Night)
- Small scale design to fit in 5" dome enclosures such as the Pelco® DF5 Housing
- Fully programmable advanced WDR
- Sensitivity of 0.0005 Lux
- Advanced OSD Functions: Motion Activated Pointing Zoom, Defog, BLC/HLC, Motion Deblur, Pixel Defect Compensation, Title Set, Mirror, Flip
- 100% Pure Digital Transmission of video data
- Up to 700' HD Transmission Range (Depending on cable characteristics and integrity)
- 12VDC / 24VAC Dual Voltage Operation

Detailed Specifications

Sensor	1/2.9" Sony® CMOS
Resolution	2.1 MegaPixel (1080p / 720p)
S/N	More than 52 dB (AGC Off)
Video Output	1x HD-SDI (BNC) / 1x SD CVBS
Lens	CS Mount Lens Support (Not Included)
Digital Zoom	1.1x ~ 8x
Minimum Illumination	0.0005 Lux (@AGC Max. DSS x2)
Day/Night	Mechanical IR Cut Filter (True Day/Night)
Electronic shutter speed	Auto (1/ 30sec ~ 1/ 60,000sec)
White Balance	ATW / ATWext / One Push / Manual
Brightness	YES
DSS (Sens-Up)	OFF / AUTO / X2 ~ X32
DNR	3D-DNR
WDR	YES
Privacy	YES (10 Zones)
Motion Detection	YES
ACE (Adaptive Color Enhancement)	YES
Advanced OSD Functions	Motion Activated Pointing Zoom, Defog, BLC/HLC, Motion Deblur, Pixel Defect Compensation, Title Set, Mirror, Flip
Communication	RS-485 (Pelco® D/P)
HD Transmission Range	Up to 700' (Depending on cable characteristics and integrity)
Operating Conditions	14°-122°F (-10°-50°C) < 80% RH
Input Voltage	12VDC / 24VAC (Dual Voltage)
Power Consumption (12VDC)	250mA (3Watt)
Power Consumption (24VAC)	230mA (2.8Watt)
Dimensions	1.89" x 2.09" x 2.89" (W x H x D)



Rear Camera Inputs



Optional Remote Control
Available (VT-UTCC)