

The VTC-LED307BB employs a 1/3" B/W CCD image device that provides extremely long life and high reliability. 12 Infrared LED's allow for clear images even in total darkness. It comes complete with lens and mounting hardware ready to install in almost any environment. 12VDC Power and compact size make the VTC-LED307BB an excellent choice for covert applications.

00.00.23

00.00.24

SUN SHROUD TO REDUCE GLARE AND

DISSIPATE HEAT



Specifications	VTC-LED307BB
Image Device	1/3" B/W CCD Image Sensor
Effective Pixels	510 x 492
Resolution	380 TV Lines
Minimum Illumination	0.25 Lux / F2.0; O Lux (Within 10 Meters IR ON)
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 to 1/100,000 Sec.
Gamma Correction	0.45
AGC	Yes
Standard Board Lens	3.6mm / F2.0
Lens Angle	85°
Video Output	Composite Output: 1.0 Vp-p / 75Ω
Power Source	12VDC (+/-10%)
Power Consumption	85 mA (IR Off) / 245 mA (IR On)
Water Resistance	IP 57
IR LED	12 Units Infrared LED
Effective Range	Over 32 Feet (10 Meters)
Dimensions	4.14" x 2.55" / 105mm x 64.6mm (L x OD)
Weight	19.4 Oz. / 550 g. / 1.21 Lbs.

9970 GLENOAKS BLVD. UNIT B SUN VALLEY, CA 91352 PHONE: 888-VITEK-70 818-771-0300 FAX: 818-771-0400 WWW.VITEKCCTV.COM