

VTM-LED220P

22" Professional Wide Screen 1080P LED Monitor with Dual Looping BNC, VGA and HDMI inputs



Included IR Remote Control



FEATURES

- 22" Wide Screen LED Display Panel
- HDMI, VGA, and Dual Looping BNC Composite Video Inputs with PC and Stereo Audio Inputs
- Resolution up to 1920 x 1080 (1080P)
- Contrast Ratio of 10,000:1
- <5ms Response time
- 170° Horizontal Viewing Angle
- Picture In Picture (PIP) / POP (Picture On Picture) Display Options
- Top Panel Controls with included IR Remote Control
- VESA 100mm Standard Mounting
- 50,000 Hour Panel Life



VTM-LED220P Rear Connections



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VTM-LED220P

22" Professional Wide Screen 1080P LED Monitor with Dual Looping BNC, VGA and HDMI inputs

| Detailed Specifications | VTM-LED220P |
|-------------------------|--|
| Screen Size | 21.5" |
| Display Type | LED |
| Aspect Ratio | 16:9 |
| Resolution | 1080P (1920x1080) |
| Response Time | <5ms |
| Contrast Ratio | 10,000:1 |
| Display Color | 16.7 Million |
| Brightness | 300cd/m ² |
| Pixel Type | Active Matrix TFT |
| Pixel Pitch | 0.2715 x 0.2715 mm |
| Viewing Angle (H/V) | 170° / 160° |
| Video System | NTSC/PAL |
| Video In/Out | 2 BNC Input / 2 BNC Output (Looping) |
| VGA In | 1 (15Pin D-Sub) |
| HDMI In | 1 |
| Audio Input | Stereo RCA & 1/8" PC |
| Built In speaker | Yes (1.5W x 2) |
| PIP / POP | Analog / Digital |
| Remote | YES |
| 3D Comb Filter | YES |
| 3D De-Interlace | YES |
| Noise Reduction | YES |
| Multi-Language | English, Spanish, German, French, Italian, Russia, Turkish, Japanese, Polish |
| Stand Tilt | 0° ~ 15° |
| Vesa Mount Size | 100mm x 100mm |
| Power Adapter | 12VDC (AC100/240 [50/60]) |
| Power Consumption | 30W Max |
| Certifications | UL, FCC-DOC, CE, ROHS |
| Operating Temperature | 32° to 104° F (0° to 40° C) |
| Operating Humidity | 10% to 90% relative, non-condensing |
| Dimensions (w/Stand) | 20.63" x 14.76" x 6.7" (524 x 375 x 170mm) |
| Weight | 7.93 lbs (3.6Kgs) |

